



1996 Beretta and Corsica Specifications - Model Availability and Dimensions

MODEL AVAILABILITY

	Beretta Coupe, Beretta Z26 Coupe and Corsica Sedan
EPA vehicle class	Compact
Assembly	Wilmington, Delaware

SPECIFICATIONS & DIMENSIONS (inches unless otherwise noted)

Exterior Dimensions	Beretta	Corsica (when differs from Beretta)
Wheelbase	103.4	
Length (overall)	187.3	183.5
Width (overall)	67.9	68.0
Height (overall)	53.0	54.0
Tread - Front	55.8	
Tread - Rear	56.6	
Minimum running ground clearance	5.6	5.7
Front overhang	42.0	38.4
Rear Overhang	41.8	41.6
Interior Front Dimensions		
Head Room	37.6	38.4
Leg Room	43.4	
Shoulder Room	53.5	54.3
Hip Room	49.6	50.7
Interior Rear Dimensions		
Head Room	36.6	37.4
Leg Room	32.6	33.8
Shoulder Room	55.2	54.8
Hip Room	50.9	51.5
Capacities		

Passenger capacity	5	
Passenger index (cu. ft.)	89.9	91.6
Cargo index (cu. ft.)	13.1	13.5
Fuel tank capacity (gal.)	15.2	
EPA interior index (cu. ft.)	103.4	105.0
Curb weight (lbs., est.)	2756/2990 (Z26)	2745/2885 (V6)



1996 Beretta and Corsica Specifications

- Chassis, Steering, Brakes, Wheels and Tires

CHASSIS SPECIFICATIONS

Chassis	Beretta/Corsica
Structure/frame	Unitized Body Frame
Body material	Steel
Suspension -- Front	
Type	MacPherson Strut w/Coil Spring
Stabilizer bar/diameter (mm)	Link/24 on Base Beretta and Corsica 22 w/V6; Link/28 w/Beretta Z26
Suspension -- Rear	
Type	Trailing Twist Axle with Tubular Control Arms, Open Section Transverse Beam and Coil Springs
Stabilizer bar/diameter (mm)	None, Link 16.5 w/Beretta Z26

STEERING

Type	Power Rack-and-Pinion
Ratio (overall)	13.96:1
Turns stop-to-stop	2.33
Turning diameter curb-to-curb (ft.)	35.3
Turning diameter wall-to-wall (ft.)	37.2

BRAKES

Type	4-Wheel ABS, Power, Front Vented Disc/Rear Drum
Gross lining, front/rear (sq. in.)	31.7/50.2
Effective area, front/rear (sq. in.)	31.7/50.2
Front disc rotor outer working diam., (in.)	10.22
Rear drum diameter x width (in.)	2.87 x 1.77
Total sweep area, front/rear (sq. in.)	182.2/86.2

WHEELS AND TIRES

Wheel type/size	Steel/14" x 6" (15" x 7" on Beretta Z26)
Tire type SBR BW	Steel-Belted Radial
Tire size (Front)	P195/70R-14 (Beretta, Corsica) or P205/60R-15 (Beretta Z26)
Spare size	T115/70D-14



1996 Beretta and Corsica Specifications - Engine, Capacities and Transmission

ENGINE SPECIFICATIONS

Model	Std. Beretta/Corsica	Std. Beretta Z26 (Opt. Beretta/Corsica)
Type	2.2 Liter SFI L4	3100 SFI V6
Block	Cast Iron	Cast Iron
Cylinder Head	Cast Aluminum	Cast Aluminum
Hydraulic lifters	Yes/Roller	Yes/Roller
Bore & Stroke (in.)	3.50 x 3.46	3.51 x 3.31
Bore & Stroke (mm)	89.0 x 88.0	89.0 x 84.01
Cam drive	Chain	Chain
Redline (rpm)	6400	5500
Displacement (liters/CID)	2.2/134	3.1/191
Compression ratio	9.0:1	9.6:1
Fuel induction	SFI	SFI
Horsepower @ engine rpm	120 @ 5200	155 @ 5200
Torque (lb.-ft.)	130 @ 4000	185 @ 4000
Exhaust System	Stainless Steel	Stainless Steel
Tailpipe(s)	Single	Dual (Single on Corsica)
Ignition System	Electronic Direct Ignition	Electronic Direct Ignition
Delcotron alternator rating	105 Amp.	105 Amp.
Battery (SAE capacity rating)	525 CCA	600 CCA
Recommend fuel (unleaded)	87 Octane	87 Octane

CAPACITIES

	Std. Beretta/Corsica	Std. Beretta Z26 (Opt. Beretta/Corsica)
Engine oil (quarts)	4.0	4.0
Engine Coolant (quarts)	9.2	12.9

TRANSMISSION SPECIFICATIONS

Models	Std. with 2.2 Liter SFI L4	Opt. with 2.2 Liter SFI L4	Std. with 3100 SFI V6
Transmission	5-Speed Manual	3-Speed Auto (Std. Corsica)	4-Speed Elect. Auto.
Layout	FWD Transverse	FWD Transverse	FWD Transverse
Gear Ratios			
1st	3.73	2.84	2.92
2nd	2.15	1.60	1.57
3rd	1.33	1.00	1.00
4th	0.92	--	0.71
5th	0.74	--	--
Reverse	3.58	2.07	2.39
Final Drive Ratios	3.83	3.18	2.93 (2.97 on Z26)



1996 Beretta and Corsica Specifications - Mileage/Performance and Trailing

MILEAGE/PERFORMANCE*

Type	2.2L SFI L4 w/ 5-Speed Manual ¹	2.2L SFI L4 w/ 3-Speed Auto	3100 SDI V6 w/ 4-Speed Elect. Auto.
Mileage			
City	25	25	21
Highway	34 31 (Corsica)	31	29
Combined	28 27 (Corsica)	27	24
Est. Cruise Range			
City	380	380	319
Highway	517 471 (Corsica)	471	441
Combined	426 410 (Corsica)	410	365

TRAILERING INFORMATION

Trailer classification	Light ²
Gross trailer weight (lbs., up to)	1000
Max tongue load (lbs.)	100

* Based on 1995 EPA ratings. 1996 ratings not available at time of publishing.

¹ - Not available on Corsica.

² - With optional 3100 V6 and 4-Speed automatic only. Trailing not recommended with 2.2 L engine.



1996 Beretta and Corsica - History by Model Year

Beretta introduced spring 1987 as 1988 model.

- ⌘ 1988 -- Beretta GTU performance model introduced
 - ⌘ 1989 -- Corsica Hatchback, Sedan and Corsica LTZ Sedan introduced
 - ⌘ 1990 -- 2.2 Liter L4 engine replaces 2.0 Liter L4 engine; 3.1 Liter V6 replaces 2.8 Liter V6; high- performance Beretta GTZ with new Quad 4 introduced, replacing Beretta GTU
 - ⌘ 1991 -- Driver air bag is a new standard feature; new interior design with new instrument panel
 - ⌘ 1992 -- 4-wheel anti-lock brake system (ABS) is introduced as standard equipment
 - ⌘ 1993 -- Brake/transmission shift interlock introduced on automatic-equipped models
 - ⌘ 1994 -- Z26 replaces GTZ; more powerful standard four-cylinder and new optional 3100 V6; new standard air conditioning, automatic door locks, redesigned front suspension introduced.
 - ⌘ 1995 -- Spring-on-center rear suspension, Daytime Running Lamps introduced.
-

