MVMA Specifications

Vehicle Line ACHIEVA
Model Year 1995 Issued 9-94 Revised (•) _____

METRIC (U.S. Customary)

Power Teams

SAE J1349 Net bhp (brake horsepower) and Net Torque corrected to 77°F/25°C and 29.61 in. Hg/100 kPa atmospheric pressure.

			A	B	C	D
ENGINE	Engine Code		LD2	LD2	LD2	L82
	Displacement Liters (in^3)		2.3 L (138) L4	2.3 L (138) L4	2.3 L (138) L4	3.1 L (191) V6
	Induction system (FI, Carb, etc.)		Mutli-Port Fuel Injection	Mutli-Port Fuel Injection	Mutli-Port Fuel Injection	Sequential Fuel Injection
	Compression ratio		9.5:1	9.5:1	9.5:1	9.6:1
	SAE Net at RPM	Power kW (bhp)	112 (150) @ 6000	112 (150) @ 6000	112 (150) @ 6000	116 (155) @ 5200
		Torque N • m (lb. ft.)	196 (145) @ 4800	196 (145) @ 4800	196 (145) @ 4800	251 (185) @ 4000
	Exhaust single, dual		Single	Single	Single	Single
TRANS	Transmission/ Transaxle		MJ1 Manual Transaxle 5-Speed	M13 Automatic Transaxle 4-Speed	MD9 Automatic Transaxle 3-Speed	M13 Automatic Transaxle 4-Speed
	Effective Final Drive / Axle Ratio (std. first)		3.94	3.69	2.84	2.93

Series Availability		Power Teams (A - B - C - D)	
Model	**Code**	**Standard**	**Optional**
ACHIEVA S			
2-Door Notchback Coupe	3NL37	A	B,C,D
4-Door Notchback Sedan	3NL69	A	B,C,D
ACHIEVA SC			
2-Door Notchback Coupe	3NF37	A	B,D
ACHIEVA SL			
2-Door Notchback Coupe	3NF69	A	B,D