

# MVMA Specifications

Vehicle Line Sebring  
 Model Year 1995 Issued 1994-11 Revised (\*) \_\_\_\_\_

## METRIC (U.S. Customary)

Model Code/Description

D41A, D42A

## Restraint System

Seating Position			Left	Center	Right
Active	Type & description (lap & shoulder belt, lap belt, etc.)  Standard / optional	First seat	3 Point seat belt with ELR	-	3 Point seat belt with ALR/ELR
		Second seat	3 Point seat belt with ALR/ELR	Lap belt	3 Point seat belt with ALR/ELR
		Third seat	-	-	-
Passive	Type & description (air bag, motorized - 2-point belt, fixed belt, knee bolster, manual - lap belt)  Standard / optional	First seat	Air bag and knee bolster		Air bag and knee bolster
		Second seat			
		Third seat			

Glass	SAE Ref. No.	
Windshield glass exposed surface area cm <sup>2</sup> (in. <sup>2</sup> )	S1	9800 (1519)
Side glass exposed surface area cm <sup>2</sup> (in. <sup>2</sup> ) - total 2-sides	S2	4023 (624)
Backlight glass exposed surface area cm <sup>2</sup> (in. <sup>2</sup> )	S3	9018 (1398)
Total glass exposed surface area cm <sup>2</sup> (in. <sup>2</sup> )	S4	22841 (3541)
Windshield glass (type / thickness)		Curved-laminated plate
Side glass (type / thickness)		Curved-tempered plate
Backlight glass (type / thickness)		Curved-tempered plate
Tinted (yes / no, location)		Yes
Solar control (yes / no, coated / batched, location)		No

## Headlamps

Description (sealed beam, halogen, replaceable bulb, etc.)	Replaceable bulb, halogen
Shape	Aerodynamic
Lo-beam type (2A1, 2B1, 2C1, etc.)	HB4-bulb
Quantity	2
Hi-beam type (1A1, 2A1, 1C1, 2C1, etc.)	HB4-bulb+HB3-bulb
Quantity	2 + 2